

SPECIFICATIONS

CHEROKEE

DESCRIPTION: Cherokee shelters, feature a gable roof, and are designed for minimum maintenance and long life in any climate. Prefabrication allows fast, easy erection over a concrete slab.

ROOF: (standard) Roll formed structural roof panels: 24" wide, W-shaped 2 ½" deep ribs on 8" centers, watertight snap-lock connection available in high strength embossed 3105 H154 aluminum or optional Galvalume® steel ASTM A792 Grade 50.
(optional) Wood. Tongue and groove decking will be Southern Yellow Pine or Western Red Cedar #1 Grade or better, kiln dried, 2" x 6" nominal dimension 5 3/8" x 1 ½" actual finished dimension with 14/32" tongue and ½" groove. To be covered with standard roofing materials. Facia is the same as the decking.
(optional) 8" flush panel, 2 5/8" deep interlocking watertight connection, smooth finish, 3105 H154 aluminum.
(optional) 3" structural insulated panel, .030 x 3105-H14/25 stucco embossed aluminum top and bottom or oriented strand board top for application of standard roofing materials and aluminum bottom bonded to a oriented 1# density expanded polystyrene is 1.1966 lb per square foot. Drip edge facia trim made from 6063-t6 aluminum extrusion 4" H.
(optional) round lattice is 2.975" outside diameter extruded aluminum tube .055" thick normally spaced 6" apart.
FACIA: (standard except for wood roof and lattice) Aluminum alloy 6063 T5 or 6105 T5 extruded gutter, trim facia, and ridge cap is included.
FASTENERS: (standard) #8-18 x ¾" #2 Tek 410SS and #12 x ¾" #3 Tek zinc plated Hex washer head screws are included for fastening fascia and roof panels.

FINISH: (standard) Steel structure will be cleaned after all welding and fabrication is completed by shot blasting to white metal, sprayed with an alkaline cleaner/phosphatizer, rinsed with ambient water, and a final rinse with a chemical sealer. Anti-graffiti finish is a polyurethane-based powder coating 3-6 mils thick that is cured at 400°F until fused into a smooth coating. The surface is made outstanding by the following qualities: Easy to clean, highly resistant to weather and corrosion, smooth flow, powder coat finish, glossy surface. This permanent protection system has been designed to withstand numerous clean-ups and its appearance will be virtually unaltered, even after repeated clean-ups, though a slight reduction in the degree of gloss is possible. Inscriptions applied with marking pens will disappear completely.
(Option for corrosive atmospheres) The above anti-graffiti finish applied over zinc rich primer 2-3 mils thick. The zinc rich primer will allow

structure to withstand up to bad environments without rusting problems. This premium finish has proven to be virtually rust free after 1000's of hours in a salt fog chamber. The zinc primer stops rust from spreading under the finish when scratches or dings occur.

(Option for areas of extreme corrosive atmosphere) Hot dip galvanizing. The steel structure is hot dip galvanized according to ASTM A 123-Zinc Coatings on Iron and Steel Products. Fabricated components are completely immersed in a bath of 98% pure molten zinc at approximately 850°F long enough to reach bath temperature. Standard powder coating is then applied.

STRUCTURE: Steel conforms to ASTM A500 or equivalent specifications.

Posts: Structural steel rectangular tubing, 3"x5"x3/16. Standard post is designed for in-ground mounting.

Optional: surface mount is available

Rafters: Structural steel tubing, 3"x3"x1/8".

INSTRUCTIONS: Complete detailed installation instructions and assembly drawings are supplied with each shelter.

OPTIONS: Bulletin Boards: Enclosed aluminum bulletin boards are manufactured with custom extruded parts engineered to provide, accurate, durable and handsome cabinets. All corners are neatly mitred and assembled with heavy duty reinforcements and fasteners. Standard features include: lockable doors, acrylic safety glass windows, continuous hinges, and natural pebble grain cork background. Optional: letters and illumination.
Aluminum seat and table top: A6063-t6 extruded aluminum 1.75" x 9.625" x .075 thick.

Expanded metal seat and table top: 2" x 2' x 14 ga. square tubing frame with round corners and 16 ga. flattened expanded steel all welded together and coated with a polyethylene copolymer based thermoplastic powder coat finish.

SHIPPING

& INSTALLATION: Shelters are pre-drilled for easy installation. The structural frame is fully fabricated to eliminate the need for drilling, cutting, or welding on site. The structure is placed on a wood skid and secured and protected by shrink wrapping. Panels and trim are packaged to prevent damage.