



P.O. Box 1290  
#2 Industrial Drive  
Salem IL 62881  
Toll Free 800-851-0865  
Fax 618-548-2890  
www.americana.com

## ALGONQUIN

**DESCRIPTION:** Algonquin park shelters are designed and constructed of aluminum alloys for minimum maintenance and long life in any climate. Prefabrication allows fast, easy erection over a concrete slab.

- **ROOF:**

- Standard - roll formed structural roof panels: 24" wide, W-shaped 2 1/2" deep ribs on 8" centers, watertight snap-lock connection available in high strength aluminum or optional Galvalume® steel ASTM A792 Grade 50.
- Option: 8" flush panel, 2 5/8" deep interlocking watertight connection, smooth finish, 3105 H154 aluminum.
- Option: 3" structural insulated panel, .030 x 3105-H14/25 stucco embossed aluminum top and bottom or oriented strand board top for application of standard roofing materials and aluminum bottom bonded to a oriented 1# density expanded polystyrene is 1.1966 lb per square foot. Drip edge fascia trim made from 6063-t6 aluminum extrusion 4" H.
- FASCIA: Aluminum alloy 6063 T5 or 6105 T5 5" tall extruded gutter, trim fascia, and ridge cap is included.
- FASTENERS: (standard) #8-18 x 3/4" #2 Tek 410SS and #12 x 3/4" #3 Tek zinc plated Hex washer head screws are included for fastening fascia and roof panels.

- **FINISH:**

- Standard steel structure will be cleaned after all welding and fabrication is completed by shot blasting to white metal, sprayed with an alkaline cleaner/phosphatizer, rinsed with ambient water, and a final rinse with a chemical sealer. Anti-graffiti finish meets AAMA 2604-2 powder coating specifications. It is 6-9 mils thick that is cured at 400°F until fused into a smooth coating. The surface is made outstanding by the following qualities: Easy to clean, highly resistant to weather and corrosion, smooth flow, powder coat finish, glossy surface. This permanent protection system has been designed to withstand numerous clean-ups and its appearance will be virtually unaltered, even after repeated clean-ups, though a slight reduction in the degree of gloss is possible. Inscriptions applied with marking pens will disappear completely.

- Corrosive atmosphere option: Above anti-graffiti finish applied over zinc rich primer 2-3 mils thick. The zinc rich primer will allow structure to withstand up to bad environments without rusting problems. This premium finish has proven to be virtually rust free after 1000's of hours in a salt fog chamber. The zinc primer stops rust from spreading under the finish when scratches or dings occur.
- Extreme corrosive atmosphere: Hot dip galvanizing. The steel structure is hot dip galvanized according to ASTM A 123-Zinc Coatings on Iron and Steel Products. Fabricated components are completely immersed in a bath of 98% pure molten zinc at approximately 850°F long enough to reach bath temperature. Standard powder coating is then applied.

- **STRUCTURE:**

- Standard post: Extruded, .1" thick, 3" square aluminum 6063T6
- Option: 1/8" x 3" x 3" steel posts are available. Standard post is designed for in-ground mounting. Optional: surface mount is available. (Steel conforms to ASTM A500 or equivalent specifications.)
- Fasteners: Steel 1/4" x 3/4" and 3/8" x 3 1/2" bolts are supplied for all shelters. Bolts, nuts and washers are hot dipped-galvanized and conform to ASTM A325

- **INSTRUCTIONS**

- Complete detailed installation instructions and assembly drawings are supplied with each shelter.

- **SHIPPING & INSTALLATION:**

- Shelters are pre-drilled for easy installation. The structural frame is fully fabricated to eliminate the need for drilling, cutting, or welding on site. The structure is placed on a wood skid and secured and protected by shrink wrapping. Panels and trim are packaged to prevent damage.